## CENTRAL INTELLIGENCE AGENCY

National Defence of the United States within the meaning of the Espionage Laws, Title

	C= O= N= I	F-T-D-E-N-T-I-A-L
OUNTRY	China	REPORT
UBJECT	Canton Shipyard	DATE DISTR. 3 April 1959
		NO. PAGES 3
		REFERENCES
		and the same of th
ATE OF NFO.		50X1-HUM
ACE & ATE ACQ.		SOX1-HUN SOX1-HUN SOX1-HUN
	COURCE EVALUATIONS ARE DEF	INITIVE. APPRAIGAL OF CONTENT TO TENTON
	production of marine engine docks for ship repair, one and another that could hand was to begin construction of Tanuary 1959: launching sit	that could accomodate vessels up to 1,000 tons  le vessels up to 5,000 tons.  The shippard 50X1-HUI  of 5,000 and 10,000-ton sea-going vessels in  les for two 5,000-ton ships and one for a 10,000-
2.	The shippard was situated of meters long, a total of 200 ander construction and by the	on a strip of land 200 meters wide and 1,000 on a square meters. Workshop buildings were
2.	The shippard was situated of meters long, a total of 200 under construction and by texpansion project was expension	ouring the first term (sic) of 1959, repair and to accommodate 10,000-ton ships.  on a strip of land 200 meters wide and 1,000 and 1,000 square meters. Workshop buildings were the end of 1958 forty percent of the shipyard 50X1-HUM
.,	The shippard was situated of meters long, a total of 200 under construction and by the expansion project was expected by 1962.	ouring the first term (sic) of 1959, repair and to accommodate 10,000-ton ships.  on a strip of land 200 meters wide and 1,000 and 1,000 square meters. Workshop buildings were the end of 1958 forty percent of the shipyard 50X1-HUM
3.	The shippard was situated of meters long, a total of 200 under construction and by the expansion project was expected by 1962.  The shippard employed a total characteristic by the end of three shifts. By the end of the shippard.  Besides shipbuilding, the shippard for purposes. In the first approach of the purposes.	ouring the first term (sic) of 1959, repair and to accommodate 10,000-ton ships.  On a strip of land 200 meters wide and 1,000 and the ship were completed to be complete; the entire ship was to the ship was
3.	The shippard was situated of meters long, a total of 200 under construction and by the expansion project was expected by 1962.  The shippard employed a total characteristic by the end of three shifts. By the end of the shippard.  Besides shipbuilding, the shippard for purposes. In the first approach of the purposes.	tal of 5,800 workers; some of the workshops were of 1959 it was expected to have 10,000 workers at the shipyard constructed boilers up to 30 tons for a struce, the shipyard would build its own turbines.
3. 4.	The shippard was situated of meters long, a total of 200 under construction and by the expansion project was expected by 1962.  The shippard employed a total construction and by the expansion project was expected by 1962.  The shippard employed a total construction by the end of the shippard.  Besides shipbuilding, the shippard context purposes. In the first a workshop for producing sets at ruction; the annual output construction; the annual output construction; the annual output construction is the shippard construction; the shippard construction is the shippard construction in the shippard con	tal of 5,800 workers; some of the workshops were on of 1959 it was expected to have 10,000 workers at shipyard constructed boilers up to 30 tons for atture, the shipyard would build its own turbines the shipyard was to be from 200,000 to 300,000 tons in of steel was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be from 200,000 to 300,000 tons in the shipyard was to be ship
3. 4.	The shippard was situated of meters long, a total of 200 under construction and by the expansion project was expected by 1962.  The shippard employed a total three shifts. By the end of the shippard.  Besides shipbuilding, the state of the purposes. In the fix A workshop for producing sestruction; the annual output C-D.	tal of 5,800 workers; some of the workshops were on 1959 it was expected to have 10,000 workers at shipyard constructed boilers up to 30 tons for atture, the shipyard would build its own turbines.  The shipyard constructed boilers up to 30 tons for atture, the shipyard would build its own turbines.  The shipyard was to be from 200,000 to 300,000 tons.  The shipyard was to be from 200,000 to 300,000 tons.  The shipyard was to be from 200,000 to 300,000 tons.  The shipyard was to be from 200,000 to 300,000 tons.  The shipyard was to be from 200,000 to 300,000 tons.  The shipyard was to be from 200,000 to 300,000 tons.

		50X1-HU
	C-O-N-F-I-D-E-N-T-I-A-L	
	<b></b> 2 <b></b>	
In t	the future, steel rolling facilities would be added.3	
		50X1-H
	No heat	
recu	uperator, known as a Cowper, was under construction or even seemed to planned. Only two furnaces,	
be p	were fitted with air blowers	50X1-HU
C () N	, the air inlet is temporarily closed with a plate. One verter for every two furnaces is to be located at the front of the	
	naces;	50X1-HL
	the state of the same from 0.1 to 10 tons	
D	the converters' capacity was to range from 0.1 to 10 tons.	
	/the converters' capacity was to range from 0.1 to 10 tons. ck walls for flame protection were being erected	
The temp	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in	
The temp	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be	50X1-HL
The temp lower	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done.	50X1-HL
The temp lower	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in	
The temp lower	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done.	50X1-HL
The temp lower	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done.	
The temp lower oper	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done,  sketch on page 3 shows the location of the Canton Shipyard,	
The temp lower oper	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done,  sketch on page 3 shows the location of the Canton Shipyard,	
The templowed open	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done,  sketch on page 3 shows the location of the Canton Shipyard,	
The templower open	overall appearance of the blast furnaces indicated that not very high peratures were planned; production and efficiency would therefore be er than with standard blast furnaces. Smaller blast furnaces were in ration in one of the buildings where casting was done;  sketch on page 3 shows the location of the Canton Shipyard;  Comments	

Sanitized Copy Approved for Release 2010/08/05 : CIA-RDP80T00246A047200370001-7

C- O- N- F- I- D- E- N- T- I- A- L

50X1-HUM

C-O-N-F-I-D-E-N-T-I-A-L


50X1-HUM

- 3 -

## Sketch of Back Reach, Canton

## Key:

- (1) Two large oil tanks approximately 20 meters in diameter and 10 meters high were observed.
- (2) Six river gumboats, approximately 18 meters long, with guns fore and aft were moored at this point.
- (3) Two large tanks similar to those seen at point (1) and seven smaller ones.
- (4) Ten oil tanks were seen here.
- (5) Canton Shipyard.
- (6) Steel works.



50X1-HUM

C-O-N-F-I-D-E-N-T-I-A-L

50X1-HUM